


Multi-Bellows Vacuum Cups


	Cup Size	Cup Material ¹	Cup Fitting		Filter	
XP-BL	30	A	-G14F		-FS	
20	Ø 20 mm	A	Ameriflex	(Blank)	None	(Blank)
30	Ø 30 mm	D	Duramax	See cup fittings for available threads.	-FD	PE Filter Disc
40	Ø 40 mm	N	Nitrile		-FS	SS Filter Screen
50	Ø 50 mm	S	Silicone		See cup fittings for availability.	

¹All cups are available in Nitrile and Silicone. Check availability for other materials before ordering.




XP-BL20

Cup Diameter: in [mm]	20 mm
Thru Hole: in [mm]	0.20 [5.1]
Stroke: in [mm]	0.51 [13.0]
Cup Weight: oz [g]	0.07 [2.0]
Internal Volume: cu in [cc]	0.24 [3.9]
Force @ 6 inHG: lb [n]	0.70 [3.1]
Force @ 18 inHG: lb [n]	1.40 [6.2]
Minimum Radius: in [mm]	0.16 [4.1]




XP-BL30

Cup Diameter: in [mm]	30 mm
Thru Hole: in [mm]	0.20 [5.1]
Stroke: in [mm]	0.79 [20.1]
Cup Weight: oz [g]	0.21 [6.0]
Internal Volume: cu in [cc]	0.80 [13.1]
Force @ 6 inHG: lb [n]	1.40 [6.2]
Force @ 18 inHG: lb [n]	3.60 [16.0]
Minimum Radius: in [mm]	0.31 [7.9]



XP-BL40

Cup Diameter: in [mm]	40 mm
Thru Hole: in [mm]	0.29 [7.4]
Stroke: in [mm]	0.98 [24.9]
Cup Weight: oz [g]	0.43 [12.2]
Internal Volume: cu in [cc]	1.6 [26.2]
Force @ 6 inHG: lb [n]	2.50 [11.1]
Force @ 18 inHG: lb [n]	4.90 [21.8]
Minimum Radius: in [mm]	0.60 [15.2]



XP-BL50

Cup Diameter: in [mm]	50 mm
Thru Hole: in [mm]	0.36 [9.1]
Stroke: in [mm]	1.10 [27.9]
Cup Weight: oz [g]	0.82 [23.2]
Internal Volume: cu in [cc]	3.40 [55.7]
Force @ 6 inHG: lb [n]	3.80 [16.9]
Force @ 18 inHG: lb [n]	9.60 [42.7]
Minimum Radius: in [mm]	0.60 [15.2]