



## MCJT SERIES COMPACT

- Ultra compact, a light weight and space saving cylinder.
- Wide range of bore sizes and strokes (12mm-100mm).
- Single and double acting available.



## MCJS SERIES Compact

- Ultra compact, a light weight and space saving cylinder.
- Wide range of bore sizes and strokes (12mm-100mm).
- Single and double acting available.
- Ideal for use in machinery where space is limited and incorporating sensor groove which enables flush fitting of sensors.
- Sensor can be mounted on any one of three faces on 12 and 16 bore and on four faces on 20-100 bore.



## MCCN SERIES Round

- Many mounting options available.
- Interchangeable with other manufacturers.




## MCGA SERIES Twin-Guided (Stop/Lift)

- Strong cylinder capable of heavy loads, used extensively for stopping work carriers in both the vertical and horizontal position.
- Large diameter guide rods enable cylinder to take high off-set loads.
- Can be used as 90 degree pusher on large conveyer systems.
- Magnetic as standard.




## MGT\* SERIES Twin-Guided

- The guide units can be assembled into cylinders that then conform to ISO6432.
- Anti-rotation guaranteed by use of external guide rods.
- Four self lube bushes or linear bearings enable high loadings and consistent movement.
- Simple to install by universal mounting holes.
- Flush fitting reed switch.
- Magnetic as standard.



## MCHA SERIES Grippers

- Available with comprehensive range of bore sizes 12-32mm.
- Highly accurate air driven device for holding work-piece.
- Magnetic as standard.





## FEATURES


- Many mounting options available.
- Interchangeable with other manufacturers.

## Specification:

Model	MCCN					
Acting type	Double acting					
Tube I.D.	20	25	32	40	50	63
Port size	NPT 1/8			NPT 1/4		
Medium	Air					
Max operating pressure	9.9 kgf/cm <sup>2</sup>					
Min operating pressure	0.5 kgf/cm <sup>2</sup>					
Test pressure	15 kgf/cm <sup>2</sup>					
Ambient temperature	- 5~ + 60 °C (No freezing)					
Lubrication	Not required					
Available speed range	50~500 mm/sec					
Cushion	With rubber cushion pad					
Sensor switch	RCA					
Sensor switch holder	BGA20	BGA25	BGA32	BGA40	BGA50	BGA63

## Order example:

**MCCN - 11 - 40 - 0425 M**




STYLE:

Code	Symbol	Description
1 1		Double acting / Male thread

## Mounting accessories:

**FAC - MCCN - 40**



MOUNTING TYPE

	LB
	CB
	FAC
	FBC
	SDB
	CB+SDB
	TA
	TB